

## Rain shower for surface-mounted ceiling installation with light 300 mm - Brushed Champagne (22kt Gold)

TARA











28 032 970



Fits: TARA, LISSÉ, VAIA, META

- rain shower Ø 300 mm
- PURE RAIN, max. flow rate 12 l/min (at 3 bar)
- PURIFY RAIN, max. flow rate 6 l/min (at 3 bar)
- Distance to ceiling from bottom edge of shower 40 mm
- with anti-scale system
- central LED Spot 3000 K
- Provided by customer: Light switch
- For simultaneous control of the jet types, we recommend the xTool thermostat module
- Not suitable for use in a steam room.

includes light bulbs with a Class F energy efficiency

	Brushed Champagne (22kt Gold)	28 032 970-46
	Chrome	28 032 970-00
	Brushed Platinum	28 032 970-06
	Platinum	28 032 970-08
	Dark Chrome	28 032 970-19
	Brushed Durabronze (23kt Gold)	28 032 970-28
	Matte Black	28 032 970-33
	Champagne (22kt Gold)	28 032 970-47
	Brushed Chrome	28 032 970-93
	Brushed Dark Platinum	28 032 970-99

## Rain shower for surface-mounted ceiling installation with light 300 mm - Brushed Champagne (22kt Gold)

TARA

28 032 970

mm [inches]



### Flow rate chart




### Certificates

LGA\_38400.

Rain shower for surface-mounted ceiling installation with light 300 mm -  
Brushed Champagne (22kt Gold)

TARA

28 032 970  
Parts for other  
finishes can be found  
here: Chrome



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
1	90 17 20 263 00 90	fixing set	1	2
2	90 24 03 309 01 90	connection	1	2
3	90 24 03 309 00 90	connection	1	2
4	90 10 01 225 00 90	electronic accessories	1	2