





LULU Shower head FlowReduce - Chrome

LULU

28 508 710



- 200mm projection
- ball-joint pivotable through 30°
- Three settings: PURIFY RAIN, COMPACT SOFT FLOW, COMPACT AQUAPRESSURE FLOW, max. flow rate 6.8 l/min (at 3 bar)
- with anti-scale system
- spray head Ø 92mm
- rosette 78 x 55 mm
- 1/2" connection
- Function from: 5 l/min
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB

	Chrome	28 508 710-00 0010
	Chrome	28 508 710-00
	Brushed Platinum	28 508 710-06 0010
	Brushed Platinum	28 508 710-06




LULU Shower head FlowReduce - Chrome


LULU

28 508 710


mm [inches]



Flow rate chart



Codes & Standards

ASME A112.18.1	cUPC	DIN 4109	EPA WaterSense
ISO 3822	Ü-Zeichen	WaterSense	



LULU Shower head FlowReduce - Chrome

LULU

28 508 710

Certificates

IAPMO_4976

IAPMO_11


LGA_38

28 508 710

Product version up to 5/15/2020

Product version from 5/15/2020

Parts for other
finishes can be found
here: Chrome





LULU Shower head FlowReduce - Chrome

LULU

28 508 710

Spare parts list

Product version up to 5/15/2020

Product version from 5/15/2020

No.	Item Number	Name	Quantity used	Delivery time
	09 27 71 004-00	rosette	5	10