

LISSE

Concealed thermostat with one function volume control - Brushed Dark Platinum

LISSE

36 425 845








Product version from 6/30/2022

cover plate 150 x 90 mm


temperature control handle with safety limit stop at 38°C

hot water temperature limiter, can be preset

WRAS

	Brushed Dark Platinum	36 425 845-99
	Chrome	36 425 845-00
	Brushed Platinum	36 425 845-06
	Dark Chrome	36 425 845-19
	Brushed Light Gold	36 425 845-27
	Matte Black	36 425 845-33
	Brushed Chrome	36 425 845-93


Recommended miscellaneous



xGRID Attachment set for integrating in the dry wall construction -

12 340 970 90

Required miscellaneous



xGRID Installation track 555 mm -


12 360 970 90

We reserve the right to change designs, product range and technical specifications without prior notice.


More information can be found at: [www.dornbracht.com](http://www.dornbracht.com) +49 (0) 2371 8899 900 mail@dornbracht.com

1/4

6/20/2025



### Flow rate chart



### Codes & Standards

DIN 4109	EN 1111	ISO 3822	Scottish Water Byelaws
UK Water Supply Regulations	Ü-Zeichen	VA-Zeichen	



LISSE Concealed thermostat with one function volume control - Brushed Dark  
Platinum

LISSE

36 425 845    Product version from 6/30/2022

Certificates and sustainability

LGA_19	ETA_20	DVGW_DW- 6512DN0	LGA_19	WRAS_250402
--------	--------	---------------------	--------	-------------

# LISSÉ Concealed thermostat with one function volume control - Brushed Dark Platinum

LISSÉ

36 425 845 Product version from 6/30/2022

