

MEM Wall-mounted basin mixer without pop-up waste - Brushed Champagne (22kt Gold)

MEM

36 707 782 Product version from 10/27/2020



- 170mm projection
- fixed spout
- rectangular, air-enriched flow
- hole diameter valve 40 mm
- hole diameter spout 40 mm
- individual rosettes 60 x 60 mm
- max. flow 5.7 l/min
- lead-free
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB
- WRAS

	Brushed Champagne (22kt Gold)	36 707 782-46
	Chrome	36 707 782-00
	Brushed Platinum	36 707 782-06
	Platinum	36 707 782-08
	Dark Chrome	36 707 782-19
	Brushed Durabronze (23kt Gold)	36 707 782-28
	Champagne (22kt Gold)	36 707 782-47
	Brushed Dark Platinum	36 707 782-99

Required miscellaneous



- Concealed wall-mounted mixer centred spout -** 35 700 970 90
- max. recess depth 150 mm
 - min. recess depth 110 mm

Required miscellaneous




- Concealed wall-mounted mixer variable positioning -** 35 720 970 90
- min. recess depth 110 mm
 - max. recess depth 150 mm

MEM Wall-mounted basin mixer without pop-up waste - Brushed Champagne (22kt Gold)

MEM

36 707 782 Product version from 10/27/2020
mm [inches]



Flow rate chart



Codes & Standards

DIN 4109

ISO 3822

Scottish Water
Byelaws

UK Water Supply
Regulations

Ü-Zeichen



MEM Wall-mounted basin mixer without pop-up waste - Brushed Champagne (22kt Gold)

MEM

36 707 782 Product version from 10/27/2020

Certificates and sustainability

LGA_18

WRAS_2204

MEM Wall-mounted basin mixer without pop-up waste - Brushed Champagne (22kt Gold)

MEM

36 707 782 Product version from 10/27/2020



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
8	90 20 78 002 06-46	handle (cold)	1.00	30
6	04 28 22 150 10-46	spout	1.00	30
7	90 29 03 109 00 90	aerator	1.00	2
4	90 21 02 108 00 90	disc	2.00	2
5	90 20 78 002 07-46	handle (hot)	1.00	30
9	90 90 03 157 00 90	top	1.00	2
3	90 27 78 035 00-46	rosette	1.00	30
2	09 24 03 081 10 90	extension	1.00	2
1	90 90 03 156 00 90	top	1.00	2
10	90 20 78 002 01-46	handle	1.00	30