


SERENITY SKY+ Rain panel for recessed ceiling installation - Brushed Dark  
Platinum

SERIES-VARIOUS

41 780 979    Product version from 9/1/2024



- exposed trim parts
- Rain panel with 5 different flow modes
- Rain panel, 600 x 420 mm
- PURIFY RAIN, 175 x 175 mm, max. flow rate 10 l/min (at 3 bar)
- FULL RAIN, 455 x 315 mm, max. flow rate 14 l/min (at 3 bar)
- LAMINAR FLOW, max. flow rate 10 l/min (at 3 bar)
- AQUAPRESSURE FLOW, max. flow rate 9.4 l/min (at 3 bar)
- COOL MIST, max. flow rate 1 l/min (at 3 bar)
- with anti-scale system

**Technical data:**

- min. recess depth 150 mm
- weight 15kg

**technical data:**

- Not suitable for use in a steam room.

**Sanitary:**

- recommended water hardness: 6-7 °dH - if the water is harder, integrate a water softener that uses the ion exchange principle into the feed pipe.
- for choosing the drainage, taking into consideration the discharge of all the products in the shower, the specific demand needs to be assessed.  
Recommendation: Floor drain (connected rating) = 1l/sec, drainage rate DN 50
- feed pipe (hot/cold): 2x DN 20
- For the optimum choice of hot water storage device - taking into consideration additional drawing-off points and the frequency with which the rain panels are used - the specific demand needs to be assessed

**Notes:**

- Recommended control element: xTool

	Brushed Dark Platinum	41 780 979-99
	Chrome	41 780 979-00
	Dark Chrome	41 780 979-19
	Brushed Bronze	41 780 979-42
	Brushed Champagne (22kt Gold)	41 780 979-46
	Champagne (22kt Gold)	41 780 979-47
	Brushed Stainless Steel	41 780 979-86

Required miscellaneous



SERENITY SKY+ Concealed ceiling installation box -

35 780 970 90


- concealed rough parts
- 5x 1/2" female connector
- flush-mounted reflection box, 662 x 482 mm, RAL 9003, Signal White
- min. recess depth 150 mm
- weight 15kg

# SERENITY SKY+ Rain panel for recessed ceiling installation - Brushed Dark Platinum


SERIES-VARIOUS

41 780 979 Product version from 9/1/2024

mm [inches]  
1:10



## Flow rate chart



## Codes & Standards

DIN 4109

ISO 3822

Scottish Water  
Byelaws

UK Water Supply  
Regulations

## Ü-Zeichen



## SERENITY SKY+ Rain panel for recessed ceiling installation - Brushed Dark Platinum

SERIES-VARIOUS

---

41 780 979 Product version from 9/1/2024

Certificates and sustainability

---

LGA\_38

WRAS\_250102



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
2	91 16 02 053 00 90	holder	1.00	2
1	90 12 01 095 00 90	shower	1.00	2
5	90 30 04 096 02 90	hose	1.00	2
6	90 30 04 096 03 90	hose	1.00	2
4	90 30 04 096 01 90	hose	1.00	2
7	90 30 04 033 00 90	hose	1.00	2
3	90 12 05 106 00-99	cover	1.00	20