

## MADISON Shower set without hand shower - Brushed Durabron (23kt Gold)

MADISON

26 413 370



- slide bar
- Pipe diameter 18 mm
- rosettes Ø 60 mm
- gauge 850 mm
- metal shower hose 1750mm with integrated anti-twist protection
- shower hose connector 1/2"
- WRAS

This article does not include a hand shower!

	Brushed Durabron (23kt Gold)	26 413 370-28
	Chrome	26 413 370-00
	Brushed Platinum	26 413 370-06
	Platinum	26 413 370-08
	Durabron (23kt Gold)	26 413 370-09
	Brushed Dark Platinum	26 413 370-99

### Recommended miscellaneous

	<b>Concealed wall elbow -</b> • max. recess depth 163 mm • min. recess depth 90 mm	35 085 970 90
--	--	---------------

### Recommended miscellaneous

	<b>MADISON Wall elbow - Brushed Durabron (23kt Gold)</b>	28 450 370-28
--	--	---------------

### Required miscellaneous

	<b>MADISON Hand shower FlowReduce - Brushed Durabron (23kt Gold)</b> • spray head Ø 95mm • Hand shower see page {PAGE} • Three settings: COMPACT RAIN, COMPACT SOFT FLOW, COMPACT AQUAPRESSURE FLOW, max. flow rate l/min (at 3 bar)	28 002 978-28 0010
--	---	--------------------

### Required miscellaneous

	<b>MADISON Metal hand shower with porcelain insert (white) FlowReduce - Brushed Durabron (23kt Gold)</b>	28 002 970-28 0010
--	--	--------------------

### Required miscellaneous

	<b>MADISON Hand shower - Brushed Durabron (23kt Gold)</b> • spray head Ø 95mm • Hand shower see page {PAGE} • Three settings: COMPACT RAIN, COMPACT SOFT FLOW, COMPACT AQUAPRESSURE FLOW, max. flow rate l/min (at 3 bar)	28 002 978-28
--	--	---------------

26 413 370



### Codes & Standards

Scottish Water  
Byelaws

UK Water Supply  
Regulations

### Certificates and sustainability

WRAS\_2009



## Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
1	05 17 97 507 00 90	fixing set	2.00	2
8	12 580 970-28	Slide unit - Brushed Durabronz (23kt Gold)	1.00	20
9	28 204 970-28	Metal shower hose 1/2" x 1/2" x 1750 mm - Brushed Durabronz (23kt Gold)	1.00	2
3	09 31 11 140 90	pin	2.00	60
6	09 18 40 009 90	sleeve	2.00	2
7	08 28 22 596-28	pipe	1.00	20
4	09 31 11 002 90	pin	2.00	2
5	09 21 40 020-28	connection	2.00	20
2	09 30 30 048 90	screw	2.00	2