











36 200 819



- rotary diverter
- rosette Ø 60 mm
- WRAS

| | | |
|---|-------------------------------|---------------|
|  | Brushed Bronze | 36 200 819-42 |
|  | Chrome | 36 200 819-00 |
|  | Brushed Platinum | 36 200 819-06 |
|  | Dark Chrome | 36 200 819-19 |
|  | Brushed Durabrass (23kt Gold) | 36 200 819-28 |
|  | Brushed Dark Brass | 36 200 819-39 |
|  | Brushed Champagne (22kt Gold) | 36 200 819-46 |
|  | Champagne (22kt Gold) | 36 200 819-47 |
|  | Brushed Dark Platinum | 36 200 819-99 |

Required miscellaneous

| | | |
|---|--|---------------|
|  | Concealed two-way diverter - •min. recess depth 85 mm •max. recess depth 160 mm | 35 202 970 90 |
|---|--|---------------|

36 200 819

mm [inches]



Flow rate chart



Codes & Standards

| | | | |
|----------|----------|---------------------------|--------------------------------|
| DIN 4109 | ISO 3822 | Scottish Water Byelaws | UK Water Supply Regulations |
|----------|----------|---------------------------|--------------------------------|

Ü-Zeichen



VAIA Concealed two-way diverter - Brushed Bronze

VAIA

36 200 819

Certificates and sustainability

LGA_38

WRAS_2307

36 200 819

