

Wall valve clockwise closing 1/2" - Dark Chrome

SERIES SPECIFIC


36 607 740



- without rosette
- handle Ø 60mm
- without marking
- head part with cut-to-length spindle and sleeve
- WRAS

|   |                               |               |
|---|-------------------------------|---------------|
|    | Dark Chrome                   | 36 607 740-19 |
|    | Chrome                        | 36 607 740-00 |
|    | Brushed Platinum              | 36 607 740-06 |
|    | Light Gold                    | 36 607 740-26 |
|    | Brushed Light Gold            | 36 607 740-27 |
|    | Brushed Durabrass (23kt Gold) | 36 607 740-28 |
|    | Matte Black                   | 36 607 740-33 |
|    | Brushed Bronze                | 36 607 740-42 |
|    | Brushed Champagne (22kt Gold) | 36 607 740-46 |
|   | Champagne (22kt Gold)         | 36 607 740-47 |
|  | Brushed Chrome                | 36 607 740-93 |
|  | Brushed Dark Platinum         | 36 607 740-99 |

Required miscellaneous

- 

Wall valve 1/2" -


•max. recess depth 145 mm

•min. recess depth 85 mm

35 607 970 90

36 607 740

mm [inches]



| Codes & Standards |          |                        |                             |
|-------------------|----------|------------------------|-----------------------------|
| ASME A112.18.1    | cUPC     | DIN 4109               | EN 1111                     |
| EN 200            | ISO 3822 | Scottish Water Byelaws | UK Water Supply Regulations |
| Ü-Zeichen         |          |                        |                             |

| Certificates and sustainability |              |        |        |           |
|---------------------------------|--------------|--------|--------|-----------|
| DVGW_DW-6501DN0                 | WRAS_2011    | LGA_38 | LGA_29 | WRAS_2010 |
| DVGW_DW-6512DN0                 | IAPMO_4976 ( |        |        |           |

36 607 740

