

## SERENITY SKY+ Rain panel for recessed ceiling installation with light - Dark Chrome

41 781 979



- exposed trim parts
- Rain panel with 5 different flow modes
- Rain panel, 600 x 420 mm
- PURIFY RAIN, 175 x 175 mm, max. flow rate 10 I/min (at 3 bar)
- FULL RAIN, 455 x 315 mm, max. flow rate 14 l/min (at 3 bar) • LAMINAR FLOW, max. flow rate 10 l/min (at 3 bar)
- AQUAPRESSURE FLOW, max. flow rate 9.4 l/min
- (at 3 bar)
- COOL MIST, max. flow rate 1 l/min (at 3 bar)
- min. recess depth 150 mm
- weight 15kg
- feed pipe (hot/cold): 2x DN 20
- with anti-scale system
- Recommended control element: xTool
- 24V DC (CV)
- ZigBee Light Link RGBW controller
- Provided by customer: Zigbee gateway
- Not suitable for use in a steam room.

35 781 970 90

includes light bulbs with a Class G energy

includes light bulbs with a Class G energy efficiency

n ) ı	Dark Chrome	41 781 979-19
	Chrome	41 781 979-00
	Brushed Bronze	41 781 979-42
	Brushed Champagne (22kt Gold)	41 781 979-46
	Champagne (22kt Gold)	41 781 979-47
	Brushed Stainless Steel	41 781 979-86
	Brushed Dark Platinum	41 781 979-99

### Required miscellaneous




#### **SERENITY SKY+ Concealed** ceiling installation box with light -


- •concealed rough parts
- •2x female thread 1/2" connections
- •flush-mounted reflection box, 662 x 482 mm, RAL 9003, Signal White
- •min. recess depth 150 mm
- •weight 15kg
- •Supply pipe 7 m
- •Input 100-240V AC 50-60Hz
- Output 24V DC SELV / Class 2
- •ZigBee Light Link RGBW controller
- •Provided by customer: Zigbee gateway



# SERENITY SKY+ Rain panel for recessed ceiling installation with light - Dark Chrome



### Flow rate chart





# SERENITY SKY+ Rain panel for recessed ceiling installation with light - Dark Chrome

41 781 979



SERENITY SKY+ Rain panel for recessed ceiling installation with light - Dark Chrome

41 781 979

**Spare parts list**