

















WATER FALL Cascade spout with individual jets for wall mounting - Brushed Bronze

SERIES-VARIOUS

13 425 979	Product version from 10/1/2023		
	<ul style="list-style-type: none"> • 22mm projection • PEARLSTREAM • plate 240 mm x 60 mm • connection 1/2", for shortening • plug-link mounting • Max. flow rate 9.5 l/min (at 3 bar) 		
			
			Brushed Bronze13 425 979-42
			Chrome13 425 979-00
			Brushed Platinum13 425 979-06
			Platinum13 425 979-08
			Dark Chrome13 425 979-19
			Light Gold13 425 979-26
			Brushed Light Gold13 425 979-27
			Brushed Durabrass (23kt Gold)13 425 979-28
			Matte Black13 425 979-33
			Brushed Dark Brass13 425 979-39
			Brushed Champagne (22kt Gold)13 425 979-46
			Champagne (22kt Gold)13 425 979-47
			Brushed Chrome13 425 979-93
			Brushed Dark Platinum13 425 979-99

Recommended miscellaneous




Concealed wall elbow -

- min. recess depth 90 mm
- max. recess depth 163 mm

35 085 970 90

Recommended miscellaneous



Concealed wall elbow -


- min. recess depth 90 mm
- max. recess depth 163 mm

35 085 970 90

WATER FALL Cascade spout with individual jets for wall mounting - Brushed Bronze

SERIES-VARIOUS

13 425 979 Product version from 10/1/2023
mm [inches]



Flow rate chart



Trajectory diagram



Codes & Standards

ASME A112.18.1

cUPC

DIN 4109

ISO 3822

Ü-Zeichen



WATER FALL Cascade spout with individual jets for wall mounting - Brushed Bronze SERIES-VARIOUS

13 425 979 Product version from 10/1/2023

Certificates and sustainability

LGA_19

IAPMO_4976



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
7	09 17 01 185 20-42	spout	1.00	60
8	90 29 03 071 00 90	insert	1.00	2
1	04 30 31 024 01 90	fixing set	1.00	2
5	90 31 20 087 00-42	plug	1.00	30
2	09 14 05 009 90	seal	1.00	2
6	09 31 11 144 90	pin	2.00	2
4	90 24 03 199 00 90	connection	1.00	2
3	09 17 97 053 90	holder	1.00	2