

TARA Bath shower set for bath rim or tile edge installation - Brushed Bronze

TARA

27 512 892 Product version from 4/1/2024



- spout: circular, air-enriched flow
- max. flow 23.5 l/min at 3 bar flow pressure
- Hand shower: COMPACT RAIN, max. flow rate 6.8 l/min (at 3 bar)
- complete hand shower set with anti-scale system
- 220mm projection
- automatic bath/shower diverter
- height of mixer 290 mm
- height up to aerator 135 mm
- hole diameter spout 32 mm
- hole diameter valve 32 mm
- hole diameter for complete hand shower set 32 mm
- rosette for spout Ø 55mm
- rosette for complete hand shower set Ø 50mm
- rosette for deck valve Ø 55mm
- metal shower hose 2250mm with integrated anti-twist protection

Also available with 260 mm or 300 mm projection on request (x-TRA SERVICE).

Intrinsic protection against back flow.

	Brushed Bronze	27 512 892-42
	Chrome	27 512 892-00
	Brushed Platinum	27 512 892-06
	Platinum	27 512 892-08
	Dark Chrome	27 512 892-19
	Brushed Durabrass (23kt Gold)	27 512 892-28
	Matte Black	27 512 892-33
	Brushed Dark Brass	27 512 892-39
	Brushed Champagne (22kt Gold)	27 512 892-46
	Champagne (22kt Gold)	27 512 892-47
	Brushed Chrome	27 512 892-93
	Brushed Dark Platinum	27 512 892-99

Recommended miscellaneous



Perfecto installation kit -

12 614 970 90

Recommended miscellaneous




Decorative caps for Perfecto - Brushed Bronze

• 1 pair

12 801 970-42



Flow rate chart



Codes & Standards

ASME A112.18.1

cUPC

DIN 4109

ISO 3822

Ü-Zeichen



TARA Bath shower set for bath rim or tile edge installation - Brushed Bronze

TARA

27 512 892 Product version from 4/1/2024

Certificates and sustainability

IAPMO_4976

LGA_18



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
2	13 512 892-42	spout	1.00	60
4	27 702 979-42	Hand shower set for bath rim or tile edge installation - Brushed Bronze	1.00	30
1	20 000 892-42	side panel	2.00	30
3	12 502 970 90	High pressure hose 1/2" x 1/2" x 400 mm -	1.00	2