

META SQUARE HOT & COLD WATER DISPENSER - Dark Chrome

META SQUARE

17 861 625 Product version from 5/28/2022



- 145mm projection
 - rigid, thermally insulated spout
 - laminar flow
 - height of mixer 249 mm
 - height up to laminar flow regulator 184 mm
 - hole diameter 35 mm
 - provides filtered, hot water up to 93°C
 - provides filtered, cold water
 - max. flow 2 l/min at 3 bar flow pressure
 - ready-to-use control unit for wall mounting (137mm x 159mm x 60mm)
 - electronic magnetic valve
 - 100-230 V, 50-60 Hz, 18 W power supply unit, incl. country-specific adapter set
 - lead-free
 - Spout ring cannot be removed.
 - This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB
- A minimum flow pressure of 3 bar is necessary for the HOT & COLD WATER DISPENSER to work perfectly in conjunction with a hot water tank and filter.**
- The installation must be above a kitchen sink.**
- The filter cartridge must be changed every six months. The installation instructions contain further information for guidance.**
- Detailed planning information and technical data can be found at www.dornbracht.com/professional**
- Not compatible with reverse osmosis filtration**

| | | |
|---|-------------------------------|---------------|
|  | Dark Chrome | 17 861 625-19 |
|  | Chrome | 17 861 625-00 |
|  | Brushed Platinum | 17 861 625-06 |
|  | Platinum | 17 861 625-08 |
|  | Durabrand (23kt Gold) | 17 861 625-09 |
|  | Brushed Durabrand (23kt Gold) | 17 861 625-28 |
|  | Matte Black | 17 861 625-33 |
|  | Brushed Champagne (22kt Gold) | 17 861 625-46 |
|  | Champagne (22kt Gold) | 17 861 625-47 |
|  | Brushed Chrome | 17 861 625-93 |
|  | Brushed Dark Platinum | 17 861 625-99 |

A minimum flow pressure of 3 bar is necessary for the HOT & COLD WATER DISPENSER to work perfectly in conjunction with a hot water tank and filter.

The installation must be above a kitchen sink.

The filter cartridge must be changed every six months. The installation instructions contain further information for guidance.

Detailed planning information and technical data can be found at www.dornbracht.com/professional

Not compatible with reverse osmosis filtration

Required miscellaneous



Hot water tank incl. filter -


12 892 970 90

Required miscellaneous




Hot water tank incl. filter -

12 892 970 90



Flow rate chart



Codes & Standards

| | | | |
|----------------|------|-----------------------------|--------|
| ASME A112.18.1 | cUPC | Executive Order no. 1007 | NSF372 |
| NSF61 | | | |



META SQUARE HOT & COLD WATER DISPENSER - Dark Chrome

META SQUARE

17 861 625 Product version from 5/28/2022

Certificates and sustainability

| | | | |
|-----------|------------|----------|---------|
| IAPMO_N-4 | IAPMO_4976 | GDV_0400 | IAPMO_6 |
|-----------|------------|----------|---------|

