

35 427 970 90

Product version from 3/13/2017



- lead-free, dezincification resistant
- 2x back flow preventer
- 2x female thread 1/2" connections
- 3x outlet G 1/2"
- dust cover
- anti-water packing
- sound and thermal insulation
- gauge 70 mm
- suitable for xGRID (when using installation track + 12 mm recess depth)
- WRAS

Can only be combined with exposed trim parts 36

427 SSS-FF

Recommended miscellaneous

xGRID Attachment set for integrating in the dry wall construction -

12 340 970 90


Required miscellaneous

xGRID Installation track 555 mm -

12 360 970 90

35 427 970 90
Product version from 3/13/2017


mm [inches]



Codes & Standards			
EN 1111	EN 1717	Scottish Water Byelaws	UK Water Supply Regulations

Certificates and sustainability		
Belgaqua_22_279_2	DVGW_DW-6512DN0	WRAS_250402

35 427 970 90 Product version from 3/13/2017



## Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
8	09 31 20 094 90	plug	1.00	2
15	04 21 02 146 00 90	cap	1.00	2
2	04 30 31 024 01 90	fixing set	2.00	2
1	09 30 30 171 90	screw	4.00	2
11	90 23 01 040 00 90	back-flow preventer	2.00	2
14	09 14 10 512 90	seal	1.00	2
4	09 31 20 092 90	plug	3.00	2
17	04 14 03 080 00 90	gasket kit	1.00	2
3	04 17 20 127 00 90	holder	1.00	2
13	09 24 03 219 90	nipple	2.00	2
9	09 14 10 112 90	seal	2.00	2
16	09 30 30 112 90	screw	3.00	2
10	04 30 11 149 00 90	plug	2.00	2
7	09 31 20 093 90	plug	1.00	2
5	09 14 10 139 90	seal	3.00	2
12	90 14 10 056 00 90	seal	2.00	2
6	04 31 20 039 11 90	plug	3.00	2