

xTOOL Concealed thermostat without volume control 1/2" - Brushed Platinum

SERIES SPECIFIC

36 501 985

Product version up to 2/2/2021



- cover plate 120 x 120 mm
- temperature control handle with safety limit stop at 38°C
- thermostat cartridge
- WRAS

	Brushed Platinum	36 501 985-06
	Chrome	36 501 985-00
	Platinum	36 501 985-08
	Dark Chrome	36 501 985-19
	Brushed Light Gold	36 501 985-27
	Brushed Durabrass (23kt Gold)	36 501 985-28
	Matte Black	36 501 985-33
	Brushed Champagne (22kt Gold)	36 501 985-46
	Champagne (22kt Gold)	36 501 985-47
	Brushed Chrome	36 501 985-93
	Brushed Dark Platinum	36 501 985-99

Required miscellaneous



xTOOL Concealed thermostat module without volume control -

35 503 970 90

•max. recess depth 160 mm

•min. recess depth 95 mm

Required miscellaneous



xGRID Installation track 555 mm -

12 360 970 90

Recommended miscellaneous




xGRID Attachment set for integrating in the dry wall construction -

12 340 970 90

xTOOL Concealed thermostat without volume control 1/2" - Brushed Platinum SERIES SPECIFIC

36 501 985 Product version up to 2/2/2021

mm [inches]



Flow rate chart



Codes & Standards

DIN 4109

EN 1111

ISO 3822

Scottish Water
Byelaws

UK Water Supply
Regulations

Ü-Zeichen




xTOOL Concealed thermostat without volume control 1/2" - Brushed Platinum

SERIES SPECIFIC

36 501 985 Product version up to 2/2/2021

Certificates and sustainability

WRAS_2011	DVGW_DW-6512DN0	LGA_29	LGA_29
-----------	-----------------	--------	--------



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
9	09 20 33 006-06	handle	1.00	10
6	04 17 33 006 00-06	handle	1.00	60
8	90 16 02 027 00 90	spring	1.00	2
10	09 30 30 159-06	screw	1.00	10
3	09 11 02 196-06	cover	1.00	60
12	12 178 970 90	Extension 46 mm -	1.00	2
11	09 30 30 160-06	screw	1.00	10
5	90 21 02 112 00-06	sleeve	1.00	10
4	90 14 10 049 00 90	seal	1.00	2
2	90 31 09 095 00 90	bar	1.00	2
7	90 21 33 011 00-13	handle	1.00	2
1	90 15 02 065 00 90	cartridge	1.00	2