

SERENITY SKY+ Rain panel for recessed ceiling installation with light -**Brushed Bronze**

41 781 979



- exposed trim parts
- Rain panel with 5 different flow modes
- Rain panel, 600 x 420 mm
- PURIFY RAIN, 175 x 175 mm, max. flow rate 10
- I/min (at 3 bar)
 FULL RAIN, 455 x 315 mm, max. flow rate 14 I/mir (at 3 bar)
- LAMINAR FLOW, max. flow rate 10 l/min (at 3 bar) • AQUAPRESSURE FLOW, max. flow rate 9.4 l/min
- COOL MIST, max. flow rate 1 l/min (at 3 bar)
- min. recess depth 150 mm
- weight 15kg
- feed pipe (hot/cold): 2x DN 20
- with anti-scale system
- Recommended control element: xTool

electrical:

- RGBW LED ambient lighting
- Electricity supply: 100-240 V AC, 50-60 Hz, 20 W
- system of protection: IP 65
- feeder 3 x 1.5mm2 NYM
- equipotential bonding 1 x 4mm2
- Must be provided by customer: Zigbee gateway
- Not suitable for use in a steam room.

includes light bulbs with a Class G energy efficiency

includes light bulbs with a Class G energy efficiency

Required miscellaneous



SERENITY SKY+ Concealed ceiling installation box with light -


35 781 970 90

- •concealed rough parts
- •2x female thread 1/2" connections
- •flush-mounted reflection box, 662 x
- 482 mm, RAL 9003, Signal White
- •min. recess depth 150 mm
- •weight 15kg
- •Supply pipe 7 m
- •Input 100-240V AC 50-60Hz
- Output 24V DC SELV / Class II
- •ZigBee Light Link RGBW controller
- •Provided by customer: Zigbee gateway


n)	Brushed Bronze	41 781 979-42
	Chrome	41 781 979-00
	Dark Chrome	41 781 979-19
	Brushed Champagne (22kt Gold)	41 781 979-46
	Champagne (22kt Gold)	41 781 979-47
	Brushed Stainless Steel	41 781 979-86
	Brushed Dark Platinum	41 781 979-99



SERENITY SKY+ Rain panel for recessed ceiling installation with light - Brushed Bronze



Flow rate chart





SERENITY SKY+ Rain panel for recessed ceiling installation with light - Brushed Bronze

41 781 979



SERENITY SKY+ Rain panel for recessed ceiling installation with light - Brushed Bronze

41 781 979

Spare parts list