

41 781 979



- exposed trim parts
- Rain panel with 5 different flow modes
- Rain panel, 600 x 420 mm
- PURIFY RAIN, 175 x 175 mm, max. flow rate 10 l/min (at 3 bar)
- FULL RAIN, 455 x 315 mm, max. flow rate 14 l/min (at 3 bar)
- LAMINAR FLOW, max. flow rate 10 l/min (at 3 bar)
  AQUAPRESSURE FLOW, max. flow rate 9.4 l/min
- AQUAPRESSURE FLOW, max. flow rate 9.4 l/mir (at 3 bar)
- COOL MIST, max. flow rate 1 l/min (at 3 bar)
- min. recess depth 150 mm
- weight 15kg
- feed pipe (hot/cold): 2x DN 20
- with anti-scale system
- Recommended control element: xTool

#### electrical:

- RGBW LED ambient lighting
- Electricity supply: 100-240 V AC, 50-60 Hz, 20 W
- system of protection: IP 65
- feeder 3 x 1.5mm2 NYM
- equipotential bonding 1 x 4mm2
- Must be provided by customer: Zigbee gateway
- Not suitable for use in a steam room.

35 781 970 90

includes light bulbs with a Class G energy efficiency

includes light bulbs with a Class G energy efficiency

### Required miscellaneous




### SERENITY SKY+ Concealed ceiling installation box with light -


- •concealed rough parts
- •2x female thread 1/2" connections •flush-mounted reflection box, 662 x
- 482 mm, RAL 9003, Signal White
- •min. recess depth 150 mm
- •weight 15kg
- •Supply pipe 7 m
- •Input 100-240V AC 50-60Hz
- Output 24V DC SELV / Class II
- •ZigBee Light Link RGBW controller
- Provided by customer: Zigbee gateway







### Flow rate chart





41 781 979



41 781 979

**Spare parts list**