

MADISON Rain shower with ceiling fixing 200 mm - Brushed Durabronz (23kt Gold)

MADISON

28 565 977



- rain shower Ø 200 mm
- PURE RAIN, max. flow rate 6.8 l/min (at 3 bar)
- distance between ceiling and lower edge of the shower 185mm
- rosette Ø 55 mm
- 1/2" connection
- with anti-scale system
- This product reduces water consumption by % (compared to requirements of EPAct '92)
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB

	Brushed Durabronz (23kt Gold)	28 565 977-28 0010
	Chrome	28 565 977-00 0010
	Brushed Platinum	28 565 977-06 0010
	Platinum	28 565 977-08 0010
	Durabronz (23kt Gold)	28 565 977-09 0010
	Brushed Dark Platinum	28 565 977-99 0010

Required miscellaneous


	Concealed wall elbow - ● max. recess depth 163 mm ● min. recess depth 90 mm	35 085 970-90 0010
---	--	-----------------------




MADISON Rain shower with ceiling fixing 200 mm - Brushed Durabronze (23kt Gold)

MADISON

28 565 977
mm [inches]



Flow rate chart



Codes & Standards


ASME
A112.18.1/CSA
B125.1

California Energy
Commission
(CEC)

28 565 977

Product version up to 12/5/2019

Product version from 12/5/2019





MADISON Rain shower with ceiling fixing 200 mm - Brushed Durabronze (23kt Gold)

MADISON

28 565 977

Spare parts list

Product version up to 12/5/2019

Product version from 12/5/2019

No.	Item Number	Name	Quantity used	Delivery time
	09 27 35 003-28	rosette	4	60