





## Rain shower with ceiling fixing 300 x 240 mm - Platinum

28 775 980 Product version from 3/13/2017



- PURE RAIN, max. flow rate 6.8 l/min (at 3 bar)
- with anti-scale system
- rain shower 300 x 240mm
- distance between ceiling and lower edge of the shower 165mm
- rosette 60 x 60, as required
- 1/2" connection
- Function from: 6 l/min
- This product reduces water consumption by 28% (compared to requirements of EPAct '92)
- This product can contribute to Water Use Reduction in LEED® Green Building Rating
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB

	Platinum	28 775 980-08 0010
	Chrome	28 775 980-00 0010
	Brushed Platinum	28 775 980-06 0010
	Dark Chrome	28 775 980-19 0010
	Brushed Durabross (23kt Gold)	28 775 980-28 0010
	Matte Black	28 775 980-33 0010
	Brushed Champagne (22kt Gold)	28 775 980-46 0010
	Champagne (22kt Gold)	28 775 980-47 0010
	Brushed Chrome	28 775 980-93 0010
	Brushed Dark Platinum	28 775 980-99 0010

### Required miscellaneous



- Concealed wall elbow -**
- max. recess depth mm
  - min. recess depth mm


35 085 970-90  
0010




# Rain shower with ceiling fixing 300 x 240 mm - Platinum

28 775 980    Product version from 3/13/2017

mm [inches]



## Flow rate chart



## Codes & Standards

ASME A112.18.1	ASME A112.18.1/CSA B125.1	California Energy Commission (CEC)	cUPC
Water Sense			



## Rain shower with ceiling fixing 300 x 240 mm - Platinum

---

28 775 980 Product version from 3/13/2017


### Certificates

---

IAPMO\_4976

# Rain shower with ceiling fixing 300 x 240 mm - Platinum

28 775 980    Product version from 3/13/2017



## Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
1	09 27 98 017-08	rosette	1	40
2	90 11 10 092 00-08	connection	1	40
3	04 12 05 063 10-08	shower	1	40