

LULU Rain shower with ceiling fixing 300 x 240 mm - Brushed Platinum

LULU

28 796 710



- PURE RAIN, max. flow rate 6.8 l/min (at 3 bar)
- Function from: 6 l/min
- with anti-scale system
- rain shower 300 x 240mm
- distance between ceiling and lower edge of the shower 165mm
- rosette 78 x 55, as required
- 1/2" connection
- quick clearing
- This product reduces water consumption by % (compared to requirements of EPAct '92)
- This product can contribute to Water Use Reduction in LEED® Green Building Rating
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB



Brushed Platinum

28 796 710-06 0010



Chrome

28 796 710-00 0010

Required miscellaneous



Concealed wall elbow -

- max. recess depth 163 mm
- min. recess depth 90 mm

35 085 970-90
0010




LULU Rain shower with ceiling fixing 300 x 240 mm - Brushed Platinum


LULU

28 796 710

mm [inches]



Flow rate chart



Codes & Standards

ASME A112.18.1	ASME A112.18.1/CSA B125.1	California Energy Commission (CEC)	cUPC
EPA WaterSense	Water Sense	WaterSense	



LULU Rain shower with ceiling fixing 300 x 240 mm - Brushed Platinum

LULU


28 796 710

Certificates

IAPMO_4976

IAPMO_11

Product version from 3/13/2017





LULU Rain shower with ceiling fixing 300 x 240 mm - Brushed Platinum

LULU

28 796 710

Spare parts list

Product version from 3/13/2017

No.	Item Number	Name	Quantity used	Delivery time
	09 27 71 020-06	rosette	3	10