

VAIA Wall-mounted valve cold water without pop-up waste - Chrome

VAIA

30 010 809



- 151mm projection
- fixed spout
- circular, air-enriched flow
- adapter with male thread 3/4"
- hole diameter 35 mm
- rosette Ø 60 mm
- max. flow 4.5 l/min
- lead-free
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB

	Chrome	30 010 809-00 0010
	Brushed Platinum	30 010 809-06 0010
	Platinum	30 010 809-08 0010
	Dark Chrome	30 010 809-19 0010
	Brushed Durabronze (23kt Gold)	30 010 809-28 0010
	Brushed Bronze	30 010 809-42 0010
	Brushed Champagne (22kt Gold)	30 010 809-46 0010
	Champagne (22kt Gold)	30 010 809-47 0010
	Brushed Dark Platinum	30 010 809-99 0010

Recommended miscellaneous




Concealed wall elbow -

- min. recess depth 90 mm
- max. recess depth 163 mm

35 085 970-90
0010

30 010 809

mm [inches]




Codes & Standards			
ADA	ASME A112.18.1	California Energy Commission (CEC)	cUPC
EPA WaterSense	NSF372	NSF61	WaterSense



Certificates and sustainability			
IAPMO_8834	IAPMO_6397	IAPMO_N-4976	IAPMO_4976 (

30 010 809



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
	2 90 90 03 175 00 90	top	1.00	2
	3 90 28 22 381 01-00	spout	1.00	10
	5 09 24 03 269 90	nipple	1.00	2
	1 90 20 66 025 00-00	handle	1.00	10
	4 90 14 10 060 00 90	seal	1.00	2