

VAIA Wall-mounted valve cold water without pop-up waste - Brushed Champagne (22kt Gold)

30 010 809



- 151mm projection
- fixed spout
- circular, air-enriched flow
- adapter with male thread 3/4"
- hole diameter 35 mm
- rosette Ø 60 mm
- max. flow 4.5 l/min
- lead-free
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB

	Brushed Champagne (22kt Gold)	30 010 809-46 0010
	Chrome	30 010 809-00 0010
	Brushed Platinum	30 010 809-06 0010
	Platinum	30 010 809-08 0010
	Dark Chrome	30 010 809-19 0010
	Brushed Durabronze (23kt Gold)	30 010 809-28 0010
	Brushed Bronze	30 010 809-42 0010
	Champagne (22kt Gold)	30 010 809-47 0010
	Brushed Dark Platinum	30 010 809-99 0010

Recommended miscellaneous




- Concealed wall elbow -**
- min. recess depth mm
 - max. recess depth mm

35 085 970-90
0010



VAIA Wall-mounted valve cold water without pop-up waste - Brushed Champagne (22kt Gold)

30 010 809
mm [inches]



Flow rate chart



Codes & Standards

ASME A112.18.1	California Energy Commission (CEC)	cUPC	NSF372
NSF61			



VAIA Wall-mounted valve cold water without pop-up waste - Brushed
Champagne (22kt Gold)

30 010 809
Certificates

IAPMO_6397 IAPMO_N-4976 IAPMO_4976 (

VAIA Wall-mounted valve cold water without pop-up waste - Brushed
Champagne (22kt Gold)

30 010 809



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
1	90 20 66 025 00-46	handle	1	30
2	90 90 03 175 00 90	top	1	2
3	90 28 22 381 01-46	spout	1	30
4	90 14 10 060 00 90	seal	1	2
5	09 24 03 269 90	nipple	1	2