












VAIA POT FILLER Cold-water valve - Durabrand (23kt Gold)

VAIA

30 805 809



- 500mm projection
- pivoting spout
- laminar flow
- cold water only
- max. flow 5.7 l/min at 3 bar flow pressure
- two valves
- min. recess depth 125 mm
- max. recess depth 80 mm
- lead-free
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB

| | | |
|--|-------------------------------|---------------|
|  | Durabrand (23kt Gold) | 30 805 809-09 |
|  | Chrome | 30 805 809-00 |
|  | Brushed Platinum | 30 805 809-06 |
|  | Platinum | 30 805 809-08 |
|  | Dark Chrome | 30 805 809-19 |
|  | Brushed Durabrand (23kt Gold) | 30 805 809-28 |
|  | Brushed Champagne (22kt Gold) | 30 805 809-46 |
|  | Champagne (22kt Gold) | 30 805 809-47 |
|  | Brushed Chrome | 30 805 809-93 |
|  | Brushed Dark Platinum | 30 805 809-99 |

Required miscellaneous



- POT FILLER Concealed wall elbow** 35 087 970-90
- 0010
- min. recess depth 80 mm
 - max. recess depth 125 mm

Flow rate chart



Codes & Standards

California Energy
Commission
(CEC)



VAIA POT FILLER Cold-water valve - Durabass (23kt Gold)

VAIA

30 805 809

Certificates

LGA_29748.