

TARA ULTRA POT FILLER Cold-water valve - Brushed Dark Platinum

TARA ULTRA

30 805 875 Product version from 10/1/2024



- 500mm projection
- pivoting spout
- laminar flow
- cold water only
- max. flow 5.7 l/min at 3 bar flow pressure
- two valves
- min. recess depth 125 mm
- max. recess depth 80 mm
- lead-free
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB
- WRAS

	Brushed Dark Platinum	30 805 875-99
	Chrome	30 805 875-00
	Brushed Platinum	30 805 875-06
	Platinum	30 805 875-08
	Durabrass (23kt Gold)	30 805 875-09
	Dark Chrome	30 805 875-19
	Brushed Durabrass (23kt Gold)	30 805 875-28
	Brushed Bronze	30 805 875-42
	Brushed Champagne (22kt Gold)	30 805 875-46
	Champagne (22kt Gold)	30 805 875-47
	Brushed Chrome	30 805 875-93

Required miscellaneous



POT FILLER Concealed wall elbow 35 087 970-90
-

0010

- max. recess depth 125 mm
- min. recess depth 80 mm

30 805 875 Product version from 10/1/2024



Flow rate chart



Codes & Standards

ASME A112.18.1	California Energy Commission (CEC)	cUPC	DIN 4109
ISO 3822	NSF372	NSF61	Scottish Water Byelaws
UK Water Supply Regulations	Ü-Zeichen		



TARA ULTRA POT FILLER Cold-water valve - Brushed Dark Platinum

TARA ULTRA

30 805 875 Product version from 10/1/2024

Certificates and sustainability

LGA_29

IAPMO_N-4

IAPMO_6

WRAS_240702

IAPMO_4976 (



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
8	90 16 04 001 00 90	spring	1.00	2
1	09 20 62 025-99	handle	1.00	20
12	09 21 02 028-99	lid	1.00	20
10	09 14 10 015 90	seal	2.00	2
6	90 30 01 213 00 90	connection	1.00	2
4	09 20 62 027-99	handle	1.00	20
2	90 90 03 146 00 90	top	1.00	2
11	09 28 10 139 90	ring	1.00	2
3	90 23 01 026 11-99	aerator	1.00	20
5	90 90 03 171 00 90	top	1.00	2
7	90 27 87 039 00-99	rosette	1.00	20
9	09 28 10 136 90	ring	1.00	2