

# WATER FAN horizontal Concealed body spray - Brushed Bronze

SERIES-VARIOUS

36 512 979 Product version from 10/1/2023

















- water jet adjustable
- forceful flat water jet
- horizontal water jet
- max. flow 6.8 l/min
- Function from: l/min

## Technical data:

- cover plate 240 x 60 mm
- 1/2" connection

## Notes:

- This product reduces water consumption by 28% (compared to requirements of EPAct '92)
- This product can contribute to Water Use Reduction in LEED® Green Building Rating
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB

	Brushed Bronze	36 512 979-42 0010
	Chrome	36 512 979-00 0010
	Brushed Platinum	36 512 979-06 0010
	Platinum	36 512 979-08 0010
	Dark Chrome	36 512 979-19 0010
	Light Gold	36 512 979-26 0010
	Brushed Light Gold	36 512 979-27 0010
	Brushed Durabronze (23kt Gold)	36 512 979-28 0010
	Matte Black	36 512 979-33 0010
	Brushed Dark Bronze	36 512 979-39 0010
	Brushed Champagne (22kt Gold)	36 512 979-46 0010
	Champagne (22kt Gold)	36 512 979-47 0010
	Brushed Chrome	36 512 979-93 0010
	Brushed Dark Platinum	36 512 979-99 0010

## Required miscellaneous



**Concealed wall installation box -** 35 206 970-90  
 • min. recess depth 100 mm 0010  
 • max. recess depth 173 mm

## Recommended miscellaneous




**xGRID Attachment set for integrating in the dry wall construction -** 12 340 970 90

## Required miscellaneous



**xGRID Installation track 555 mm -** 12 360 970 90

mm [inches]




Codes & Standards

ASME A112.18.1	California Energy Commission (CEC)	cUPC
----------------	--	------

Certificates and sustainability

IAPMO\_4976 (



**Spare parts list**

No.	Item Number	Name	Quantity used	Delivery time
4	09 24 05 015 90	nipple	1.00	2
5	09 23 01 165 90	flow reducer	1.00	2
1	90 27 99 002 00-42	insert	1.00	20
3	09 14 10 003 90	seal	1.00	2
6	09 16 01 014 90	ring	1.00	2
2	90 31 10 012 00 90	insert	1.00	2