















WATER FALL Cascade spout with individual jets for wall mounting - Dark Chrome

SERIES-VARIOUS

13 425 979	<ul style="list-style-type: none"> • 22mm projection • PEARLSTREAM • plate 240 mm x 60 mm • connection 1/2", for shortening • plug-link mounting • Max. flow rate 9.5 l/min (at 3 bar) 	<div>  Dark Chrome 13 425 979-19 </div> <div>  Chrome 13 425 979-00 </div> <div>  Brushed Platinum 13 425 979-06 </div> <div>  Platinum 13 425 979-08 </div> <div>  Light Gold 13 425 979-26 </div> <div>  Brushed Light Gold 13 425 979-27 </div> <div>  Brushed Durabrass (23kt Gold) 13 425 979-28 </div> <div>  Matte Black 13 425 979-33 </div> <div>  Brushed Bronze 13 425 979-42 </div> <div>  Brushed Champagne (22kt Gold) 13 425 979-46 </div> <div>  Champagne (22kt Gold) 13 425 979-47 </div> <div>  Brushed Chrome 13 425 979-93 </div> <div>  Brushed Dark Platinum 13 425 979-99 </div>
------------	--	--

Required miscellaneous

<div> Concealed adapter - </div> <div>  </div>	35 080 970-90 0010
---	-----------------------

WATER FALL Cascade spout with individual jets for wall mounting - Dark Chrome

SERIES-VARIOUS

13 425 979
mm [inches]



Flow rate chart



Trajectory diagram



Codes & Standards

ASME A112.18.1

cUPC

DIN 4109

ISO 3822

Ü-Zeichen



WATER FALL Cascade spout with individual jets for wall mounting - Dark
Chrome

SERIES-VARIOUS

13 425 979

Certificates and sustainability

LGA_19

IAPMO_4976

