

MADISON

25 943 360



- 245mm projection
- spout: rectangular normal flow
- Hand shower: COMPACT RAIN, max. flow rate 6.8 I/min (at 3 bar)
- hand shower with anti-scale system
- rotary diverter for bath/shower
- wall bracket
- total height 901 mm
- stand pipes height 730 mm
- height up to aerator 610 mm
- slide-on rosettes Ø 90 mm
- gauge 153 mm
- metal shower hose 1250mm with integrated antitwist protection
 • max. flow 51 l/min at 3 bar flow pressure
- WRAS 1911027

Intrinsic protection against back flow.

Note: Local building codes may require the use of an anti-scald device. Please refer to remote pressure balance valve (35 910 970 90)

Intrinsic protection against back flow.

Note: Local building codes may require the use of an anti-scald device. Please refer to remote pressure balance valve (35 910 970 90)

Required miscellaneous



Concealed floor mounting -


•max. recess depth 160 mm •min. recess depth 80 mm

35 951 970-90 0010


	Durabrass (23kt Gold)	25 943 360-09
3	Chrome	25 943 360-00
	Brushed Platinum	25 943 360-06
	Platinum	25 943 360-08
	Brushed Durabrass (23kt Gold)	25 943 360-28
	Brushed Dark Platinum	25 943 360-99







Flow rate chart



Codes & Standards

ASME A112.18.1 ASME CUPC EN 1717

A112.18.1/CSA

B125.1

Scottish Water UK Water Supply Byelaws Regulations



MADISON

25 943 360 Certificates

IAPMO_4976


WRAS_1911

Belgaqua_21-378-2





25 943 360





MADISON

25 943 360

Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
	28 002 970-09	MADISON Metal hand shower with porcelain insert	43	40
		(white) - Durabrass (23kt Gold)		