

**Body spray without volume control FlowReduce - Durabrass (23kt Gold)**















TARA

28 518 979



- spray head Ø 55mm
- ball-joint pivotable through 25° (in any direction)
- HORIZONTAL RAIN, max. flow rate 5 l/min (at 3 bar)
- with anti-scale system
- rosette Ø 55 mm
- 1/2" connection
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB

Fits: TARA, LISSÉ, VAIA, META

	Durabrass (23kt Gold)	28 518 979-09
	Chrome	28 518 979-00
	Brushed Platinum	28 518 979-06
	Platinum	28 518 979-08
	Dark Chrome	28 518 979-19
	Light Gold	28 518 979-26
	Brushed Light Gold	28 518 979-27
	Brushed Durabrass (23kt Gold)	28 518 979-28
	Matte Black	28 518 979-33
	Brushed Bronze	28 518 979-42
	Brushed Champagne (22kt Gold)	28 518 979-46
	Champagne (22kt Gold)	28 518 979-47
	Brushed Chrome	28 518 979-93
	Brushed Dark Platinum	28 518 979-99

**Required miscellaneous**


**Concealed adapter -**

35 080 970-90  
0010




28 518 979


mm [inches]



Flow rate chart



Trajectory diagram



Codes & Standards

ASME  
A112.18.1/CSA  
B125.1

California Energy  
Commission  
(CEC)



Body spray without volume control FlowReduce - Durabrass (23kt Gold)

---

TARA


28 518 979

Certificates

---

IAPMO\_4976 (4). LGA\_38651.

28 518 979



### Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
1	90 14 10 026 00 90	seal	1	2
2	09 27 22 019-09	092722019-09	1	60
3	09 23 30 026-09	nut	1	40
4	09 14 15 010 90	ring	1	2
5	09 16 01 014 90	ring	1	2
6	09 23 01 048 90	back-flow preventer	1	2
7	09 21 40 016-09	connection	1	40
8	09 14 10 015 90	seal	1	2
9	90 12 05 027 00-09	casing ( completely )	1	-

Spare part can no longer be ordered, please order the replacement item