

35 429 970 Product version from 1/1/2025



- pre-seal
- lead-free, dezincification resistant
- 2x back flow preventer
- 2x supply connection 1/2" female thread (cold/hot), DN 15
- 3x outlet G 1/2"
- dust cover
- anti-water packing
- sound and thermal insulation
- gauge 70 mm
- suitable for xGRID (when using installation track + 12 mm recess depth)
- single flow function only


Can only be combined with exposed trim parts 36 427 SSS-FF or 36 428 SSS-FF.


## Concealed thermostat for three-way outlets

SERIES SPECIFIC

35 429 970 Product version from 1/1/2025

mm [inches]





### Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
	14 04 21 02 146 00 90	cap	1.00	2
	11 90 23 01 040 00 90	back-flow preventer	1.00	2
	5 09 14 10 139 90	seal	1.00	2
	1 09 30 30 171 90	screw	1.00	2
	8 09 31 20 094 90	plug	1.00	2
	2 04 30 31 024 01 90	fixing set	1.00	2
	9 09 14 10 112 90	seal	1.00	2
	13 09 14 10 512 90	seal	1.00	2
	10 04 30 11 149 00 90	plug	1.00	2
	6 04 31 20 039 11 90	plug	1.00	2
	12 04 29 05 031 01 90	insert	1.00	2
	3 04 17 20 127 00 90	holder	1.00	2
	4 09 31 20 092 90	plug	1.00	2
	15 09 30 30 112 90	screw	1.00	2
	16 04 14 03 080 00 90	gasket kit	1.00	2
	7 09 31 20 093 90	plug	1.00	2