


## WATER BAR Concealed body spray FlowReduce - Dark Chrome

SERIES-VARIOUS

36 517 979



- HORIZONTAL RAIN, max. flow rate 6 l/min (at 3 bar)
- with anti-scale system
- cover plate 240 x 60 mm
- 1/2" connection
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB
- WRAS

	Dark Chrome	36 517 979-19
	Chrome	36 517 979-00
	Brushed Platinum	36 517 979-06
	Platinum	36 517 979-08
	Light Gold	36 517 979-26
	Brushed Light Gold	36 517 979-27
	Brushed Durabronze (23kt Gold)	36 517 979-28
	Matte Black	36 517 979-33
	Brushed Bronze	36 517 979-42
	Brushed Champagne (22kt Gold)	36 517 979-46
	Champagne (22kt Gold)	36 517 979-47
	Brushed Chrome	36 517 979-93
	Brushed Dark Platinum	36 517 979-99

### Required miscellaneous



**Concealed wall installation box -** 35 206 970-90  
 • min. recess depth 100 mm 0010  
 • max. recess depth 173 mm

### Recommended miscellaneous



**xGRID Attachment set for integrating in the dry wall construction -** 12 340 970 90


### Required miscellaneous




**xGRID Installation track 555 mm -** 12 360 970 90

36 517 979


mm [inches]



**Flow rate chart**



**Trajectory diagram**



**Codes & Standards**

California Energy  
Commission  
(CEC)

DIN 4109

ISO 3822

Ü-Zeichen



## WATER BAR Concealed body spray FlowReduce - Dark Chrome

---

SERIES-VARIOUS

36 517 979

Certificates and sustainability

---

LGA\_19

