





Dornbracht Montageanleitung


Installation instructions
Montageaanwijzing
Instructions de montage
Istruzioni di montaggio
Instrucciones de montaje
Assembly Instructions
Monteringsanvisning
Montážní návod
Instrukcja montażu
Инструкция по монтажу
安装指导




Lieferumfang // Parts supplied // Omvang van de levering // Pièces livrées // Entità di fornitura // Volumen de suministro // Parts Supplied // Leveransomfang // Rozsah dodávky // Zakres dostawy // Объем поставки // 供货范围





Planungshinweis // Planning note // Aanwijzing m.b.t. de planning // Indication de réalisation // Indicazione per la progettazione // Indicación de planificación // Planning note // Planeringsanvisning // Pokyn k plánování // Wskazówka dla projektowania // Указание по планированию // 规划说明





Inch = mm x 0,0394
























mm

Inch = mm x 0,0394

(DE) Betriebsbedingungen

Maximale Vorlauftemperatur ≤ 90°C

Maximale Durchflussmenge > 25 l./min.

(GB) Operating conditions

Maximum flow temperature ≤ 90°C

Maximum flow rate > 25 l./min.

(NL) Voorwaarden voor het gebruik

Maximale voorlooptemperatuur ≤ 90°C

Maximum debiet > 25 l./min.

(FR) Conditions d'utilisation

Température maximale de l'eau

d'alimentation ≤ 90°C

Débit maximale > 25 l/min

(IT) Condizioni di funzionamento

Temperatura di mandata massima ≤ 90°C

Portata massima > 25 l./min.

(ES) Condiciones de operación

Temperatura máxima de entrada ≤ 90°C

Caudal máxima > 25 l/min

(US) Operating conditions

Maximum flow temperature ≤ 194°F

Maximum flow rate > 25 l./min.

(SE) Driftsvillkor

Max. inloppstemperatur ≤ 90 °C

Max. genomströmningsmängd > 25 l/min

(CZ) Provozní podmínky

Maximální přívodní teplota ≤ 90°C

Maximální průtok > 25 l/min.

(PL) Warunki robocze

Maksymalna temperatura zasilania ≤ 90°C

Maksymalna ilość przepływu > 25 l/min

(RU) Условия эксплуатации


Максимальная предварительная температура ≤ 90°C

Максимальная расход > 25 л/мин

(CN) 运行条件

最高进水温度 ≤ 90° C

最大流量 > 25 升/分钟



Dornbracht AG & Co. KG
Köbbingser Mühle 6, D-58640 Iserlohn
Tel. +49(0)237 1433-0, Fax +49(0)237 1433-232
mail@dornbracht.de, dornbracht.com



01 03 05 740 00 / 08.2021