
















## Wall elbow - Dark Chrome

28 450 625



- 3/8" shower outlet
- rosette Ø 55 mm
- 1/2" connection
- WRAS

Intrinsic protection against back flow.

	Dark Chrome	28 450 625-19
	Chrome	28 450 625-00
	brushed chrome	28 450 625-04
	Brushed Platinum	28 450 625-06
	Platinum	28 450 625-08
	Light Gold	28 450 625-26
	Brushed Light Gold	28 450 625-27
	Brushed Durabronze (23kt Gold)	28 450 625-28
	Matte Black	28 450 625-33
	Brushed Bronze	28 450 625-42
	aluminium	28 450 625-45
	Brushed Champagne (22kt Gold)	28 450 625-46
	Champagne (22kt Gold)	28 450 625-47
	Brushed Chrome	28 450 625-93
	Brushed Dark Platinum	28 450 625-99

## Recommended miscellaneous



- Concealed wall elbow -**
- max. recess depth mm
  - min. recess depth mm


35 085 970 90



Wall elbow - Dark Chrome

28 450 625

mm [inches]



Flow rate chart



Codes & Standards

ASME A112.18.1	cUPC	EN 1717	Scottish Water Byelaws
----------------	------	---------	------------------------

UK Water Supply Regulations



## Wall elbow - Dark Chrome

---

28 450 625

### Certificates

---

Belgaqua\_21-381-2 IAPMO\_4976

WRAS\_240702

## Wall elbow - Dark Chrome

28 450 625

