


VAIA POT FILLER Cold-water valve - Brushed Champagne (22kt Gold)

VAIA

30 805 809 Product version from 7/1/2023



- 500mm projection
- pivoting spout
- laminar flow
- cold water only
- max. flow 5.7 l/min at 3 bar flow pressure
- min. recess depth 125 mm
- max. recess depth 80 mm
- lead-free
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB
- WRAS

| | | |
|---|--------------------------------|---------------|
|  | Brushed Champagne (22kt Gold) | 30 805 809-46 |
|  | Chrome | 30 805 809-00 |
|  | Brushed Platinum | 30 805 809-06 |
|  | Platinum | 30 805 809-08 |
|  | Durabronze (23kt Gold) | 30 805 809-09 |
|  | Dark Chrome | 30 805 809-19 |
|  | Brushed Durabronze (23kt Gold) | 30 805 809-28 |
|  | Brushed Bronze | 30 805 809-42 |
|  | Champagne (22kt Gold) | 30 805 809-47 |
|  | Brushed Chrome | 30 805 809-93 |
|  | Brushed Dark Platinum | 30 805 809-99 |

Required miscellaneous

POT FILLER Concealed wall elbow 35 087 970 90



- min. recess depth 80 mm
- max. recess depth 125 mm

Flow rate chart



| Codes & Standards | | | |
|-------------------|-------|------------------------|-----------------------------|
| ASME A112.18.1 | cUPC | DIN 4109 | ISO 3822 |
| NSF372 | NSF61 | Scottish Water Byelaws | UK Water Supply Regulations |
| Ü-Zeichen | | | |



VAIA POT FILLER Cold-water valve - Brushed Champagne (22kt Gold)

VAIA

30 805 809 Product version from 7/1/2023

Certificates and sustainability

| | | | | |
|--------|--------------|-------------|------------|--------------|
| LGA_29 | IAPMO_N-4976 | WRAS_240702 | IAPMO_6397 | IAPMO_4976 (|
|--------|--------------|-------------|------------|--------------|

