














## WATER FALL Cascade spout for wall mounting - Dark Chrome

SERIES-VARIOUS

13 420 979



- 120mm projection
- CASCADE, max. flow rate 26.5 l/min (at 3 bar)
- cover plate 240 x 60 mm
- 1/2" connection
- plug-link mounting
- WRAS

|   |                                     |               |
|---|-------------------------------------|---------------|
|    | Dark Chrome                         | 13 420 979-19 |
|    | Chrome                              | 13 420 979-00 |
|    | Brushed Platinum                    | 13 420 979-06 |
|    | Platinum                            | 13 420 979-08 |
|    | Light Gold                          | 13 420 979-26 |
|    | Brushed Light Gold                  | 13 420 979-27 |
|    | Brushed Durabronze<br>(23kt Gold)   | 13 420 979-28 |
|    | Matte Black                         | 13 420 979-33 |
|    | Brushed Dark<br>Brass               | 13 420 979-39 |
|   | Brushed Bronze                      | 13 420 979-42 |
|  | Brushed<br>Champagne (22kt<br>Gold) | 13 420 979-46 |
|  | Champagne (22kt<br>Gold)            | 13 420 979-47 |
|  | Brushed Chrome                      | 13 420 979-93 |

### Recommended miscellaneous



- Concealed wall elbow -**
- max. recess depth 163 mm
  - min. recess depth 90 mm

35 085 970 90

### Recommended miscellaneous



- Concealed wall elbow -**
- max. recess depth 163 mm
  - min. recess depth 90 mm

35 085 970 90

13 420 979

mm [inches]



**Flow rate chart**



**Trajectory diagram**



**Codes & Standards**

ASME A112.18.1

cUPC

DIN 4109

ISO 3822

Ü-Zeichen



## WATER FALL Cascade spout for wall mounting - Dark Chrome

---

SERIES-VARIOUS

13 420 979

Certificates and sustainability

---

LGA\_18

IAPMO\_4976

