

## Hand shower FlowReduce -

IMO

28 018 979



- Three or five settings: COMPACT RAIN, COMPACT SOFT FLOW, COMPACT AQUAPRESSURE FLOW, max. flow rate 6.8 l/min (at 3 bar)
- with anti-scale system
- spray head Ø 100mm
- 1/2" connection
- Function from: 6 l/min
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB

Fits: IMO, LULU, MADISON, MEM, TARA, CL.1, LISSÉ, VAIA, META, CYO

Intrinsic protection against back flow.

28 018 979-43 0010

 Chrome 28 018 979-00

 Chrome 28 018 979-00 0010

 Brushed Platinum 28 018 979-06

 Brushed Platinum 28 018 979-06 0010

 Platinum 28 018 979-08

 Platinum 28 018 979-08 0010

 Dark Chrome 28 018 979-19

 Dark Chrome 28 018 979-19 0010


 Light Gold 28 018 979-26 0010

 Light Gold 28 018 979-26

 Brushed Light Gold 28 018 979-27 0010

 Brushed Light Gold 28 018 979-27

 Brushed Durabrass (23kt Gold) 28 018 979-28

 Brushed Durabrass (23kt Gold) 28 018 979-28 0010

 Matte Black 28 018 979-33


 Matte Black 28 018 979-33 0010

 Brushed Bronze 28 018 979-42

 Brushed Bronze 28 018 979-42 0010

 Brushed Champagne (22kt Gold) 28 018 979-46

 Brushed Champagne (22kt Gold) 28 018 979-46 0010

 Champagne (22kt Gold) 28 018 979-47

 Champagne (22kt Gold) 28 018 979-47 0010

 Brushed Chrome 28 018 979-93

 Brushed Chrome 28 018 979-93 0010

 Brushed Dark Platinum 28 018 979-99



Hand shower FlowReduce -

IMO

28 018 979



Brushed Dark  
Platinum


28 018 979-99 0010

## Hand shower FlowReduce -

IMO

28 018 979

mm [inches]



## Flow rate chart



## Codes & Standards

DIN 4109

ISO 3822

Ü-Zeichen



## Hand shower FlowReduce -

IMO

28 018 979

### Certificates

LGA\_29



## Hand shower FlowReduce -

---

IMO

28 018 979



Hand shower FlowReduce -

IMO

28 018 979

## Spare parts list