














## Two-way diverter for bath rim or tile edge installation - Brushed Platinum

SERIES SPECIFIC

29 140 670 Product version from 6/30/2015



- automatic bath/shower diverter
- hole diameter 32 mm
- rosette 60 x 60 mm
- 1/2" connection
- max. flow 64.9 l/min at 3 bar flow pressure
- WRAS

|   |                                |               |
|---|--------------------------------|---------------|
|    | Brushed Platinum               | 29 140 670-06 |
|    | Chrome                         | 29 140 670-00 |
|    | Platinum                       | 29 140 670-08 |
|    | Dark Chrome                    | 29 140 670-19 |
|    | Brushed Light Gold             | 29 140 670-27 |
|    | Brushed Durabronze (23kt Gold) | 29 140 670-28 |
|    | Matte Black                    | 29 140 670-33 |
|    | Brushed Dark Bronze            | 29 140 670-39 |
|    | Brushed Champagne (22kt Gold)  | 29 140 670-46 |
|   | Champagne (22kt Gold)          | 29 140 670-47 |
|  | Brushed Chrome                 | 29 140 670-93 |
|  | Brushed Dark Platinum          | 29 140 670-99 |

29 140 670 Product version from 6/30/2015

mm [inches]



### Flow rate chart



### Codes & Standards

|                |      |          |          |
|----------------|------|----------|----------|
| ASME A112.18.1 | cUPC | DIN 4109 | ISO 3822 |
|----------------|------|----------|----------|

|                           |                                |           |
|---------------------------|--------------------------------|-----------|
| Scottish Water<br>Byelaws | UK Water Supply<br>Regulations | Ü-Zeichen |
|---------------------------|--------------------------------|-----------|



Two-way diverter for bath rim or tile edge installation - Brushed Platinum

SERIES SPECIFIC

---

29 140 670    Product version from 6/30/2015

Certificates and sustainability

---

WRAS\_1911

LGA\_29

IAPMO\_4976

