

# META SQUARE HOT & COLD WATER DISPENSER - Durabrand (23kt Gold)

META SQUARE

17 861 625 Product version from 5/28/2022



- 145mm projection
  - rigid, thermally insulated spout
  - laminar flow
  - height of mixer 249 mm
  - height up to laminar flow regulator 184 mm
  - hole diameter 35 mm
  - provides filtered, hot water up to 93°C
  - provides filtered, cold water
  - max. flow 2 l/min at 3 bar flow pressure
  - ready-to-use control unit for wall mounting (137mm x 159mm x 60mm)
  - electronic magnetic valve
  - 100-230 V, 50-60 Hz, 18 W power supply unit, incl. country-specific adapter set
  - lead-free
  - Spout ring cannot be removed.
  - This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB
- A minimum flow pressure of 3 bar is necessary for the HOT & COLD WATER DISPENSER to work perfectly in conjunction with a hot water tank and filter.**
- The installation must be above a kitchen sink.**
- The filter cartridge must be changed every six months. The installation instructions contain further information for guidance.**
- Detailed planning information and technical data can be found at [www.dornbracht.com/professional](http://www.dornbracht.com/professional)**
- Not compatible with reverse osmosis filtration**

|   |                               |               |
|---|-------------------------------|---------------|
|    | Durabrand (23kt Gold)         | 17 861 625-09 |
|    | Chrome                        | 17 861 625-00 |
|    | Brushed Platinum              | 17 861 625-06 |
|    | Platinum                      | 17 861 625-08 |
|    | Dark Chrome                   | 17 861 625-19 |
|    | Brushed Durabrand (23kt Gold) | 17 861 625-28 |
|    | Matte Black                   | 17 861 625-33 |
|    | Brushed Champagne (22kt Gold) | 17 861 625-46 |
|    | Champagne (22kt Gold)         | 17 861 625-47 |
|   | Brushed Chrome                | 17 861 625-93 |
|  | Brushed Dark Platinum         | 17 861 625-99 |

A minimum flow pressure of 3 bar is necessary for the HOT & COLD WATER DISPENSER to work perfectly in conjunction with a hot water tank and filter.

The installation must be above a kitchen sink.

The filter cartridge must be changed every six months. The installation instructions contain further information for guidance.

Detailed planning information and technical data can be found at [www.dornbracht.com/professional](http://www.dornbracht.com/professional)

Not compatible with reverse osmosis filtration

## Required miscellaneous



Hot water tank incl. filter -

12 892 970 90

## Required miscellaneous



Hot water tank incl. filter -

12 892 970 90

17 861 625 Product version from 5/28/2022



**Flow rate chart**



**Codes & Standards**

ASME A112.18.1

cUPC

Executive Order  
no. 1007

NSF372

NSF61



META SQUARE HOT & COLD WATER DISPENSER - Durabross (23kt Gold)

META SQUARE

17 861 625 Product version from 5/28/2022

Certificates and sustainability

IAPMO\_N-4

GDV\_0400

IAPMO\_6

IAPMO\_4976 (

