

Concealed single-lever mixer with integrated shower connection - Brushed Chrome
SERIES-VARIOUS

36 050 970

Product version from 10/1/2023

Required miscellaneous

	Concealed wall mounting - <ul style="list-style-type: none"> min. recess depth 80 mm max. recess depth 105 mm 	35 050 970 90
--	---	---------------

Concealed single-lever mixer with integrated shower connection - Brushed Chrome

SERIES-VARIOUS

36 050 970 Product version from 10/1/2023
mm [inches]



Flow rate chart



Codes & Standards

DIN 4109

EN 1717

ISO 3822

Scottish Water
Byelaws

UK Water Supply
Regulations

Ü-Zeichen



Concealed single-lever mixer with integrated shower connection - Brushed Chrome


SERIES-VARIOUS

36 050 970 Product version from 10/1/2023

Certificates and sustainability

Belgaqua_21-025-2 WRAS_2011

LGA_29



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
12	09 18 40 230 90	connection	1.00	2
13	09 14 10 061 90	seal	1.00	2
5	09 23 01 131 90	back-flow preventer	1.00	2
2	09 24 04 266 90	nut	1.00	2
6	09 14 10 213 90	seal	1.00	2
7	09 24 03 281-93	nipple	1.00	20
10	28 322 970-93	Metal shower hose 1/2" x 3/8" x 1750 mm - Brushed Chrome	1.00	20
1	90 20 97 064 00-93	handle	1.00	20
4	09 31 11 004 90	pin	1.00	60
11	90 14 10 060 00 90	seal	1.00	2
9	90 14 20 026 00 90	seal	1.00	2
8	90 21 02 069 00-93	cover	1.00	20
3	90 15 05 044 04 90	cartridge	1.00	2