

Concealed single-lever mixer with diverter - Chrome

SERIES SPECIFIC


36 120 670    Product version up to 3/15/2019




- automatic diverter
- cover plate 150 x 90 mm
- WRAS

	Chrome	36 120 670-00
	Brushed Platinum	36 120 670-06
	Platinum	36 120 670-08
	Dark Chrome	36 120 670-19
	Brushed Light Gold	36 120 670-27
	Brushed Durabrass (23kt Gold)	36 120 670-28
	Matte Black	36 120 670-33
	Brushed Champagne (22kt Gold)	36 120 670-46
	Champagne (22kt Gold)	36 120 670-47
	Brushed Chrome	36 120 670-93
	Brushed Dark Platinum	36 120 670-99


Required miscellaneous

	<b>Concealed single-lever mixer -</b> •max. recess depth 105 mm •min. recess depth 80 mm	35 020 970 90
---	--	---------------


Recommended miscellaneous

	<b>xGRID Attachment set for integrating in the dry wall construction -</b>	12 340 970 90
---	--	---------------

Required miscellaneous

	<b>Concealed single-lever mixer with backflow preventor -</b> •max. recess depth 105 mm •min. recess depth 80 mm	35 021 970 90
---	--	---------------

Required miscellaneous

	<b>xGRID Installation track 555 mm -</b>	12 360 970 90
---	--	---------------

## Concealed single-lever mixer with diverter - Chrome

SERIES SPECIFIC

36 120 670 Product version up to 3/15/2019

mm [inches]



### Flow rate chart



### Codes & Standards

DIN 4109

ISO 3822

Scottish Water  
Byelaws

UK Water Supply  
Regulations

Ü-Zeichen



## Concealed single-lever mixer with diverter - Chrome

SERIES SPECIFIC

36 120 670 Product version up to 3/15/2019

Certificates and sustainability

LGA\_19

WRAS\_2207



## Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
6	09 11 02 260-00	sleeve	1.00	10
5	09 11 02 258-00	plate	1.00	10
11	90 21 34 081 00 90	diverter	1.00	2
10	90 31 09 139 00-00	pull-rod	1.00	10
3	09 24 04 448 90	nut	1.00	2
2	04 28 10 149 00 90	accessories	1.00	2
7	09 20 67 007-00	handle	1.00	10
4	09 14 10 084 90	seal	1.00	2
8	09 31 11 099 90	pin	1.00	2
1	90 15 05 038 00 90	cartridge	1.00	60
9	90 31 20 109 00 90	plug	1.00	2
12	90 30 09 064 00 90	key	1.00	2