

**Rain shower for surface-mounted ceiling installation 300 x 240 mm - Platinum** **SERIES SPECIFIC**

28 041 980 Product version from 5/1/2022



- rain shower 300 x 240mm
  - PURE RAIN, max. flow rate 12 l/min (at 3 bar)
  - PURIFY RAIN, max. flow rate 6 l/min (at 3 bar)
  - with anti-scale system
- Technical data:**
- Distance to ceiling from bottom edge of shower 40 mm
- Planning tips:**
- For simultaneous control of the jet types, we recommend the xTool thermostat module
  - Not suitable for use in a steam room.
  - WRAS

	Platinum	28 041 980-08
	Chrome	28 041 980-00
	Brushed Platinum	28 041 980-06
	Brushed Durabrass (23kt Gold)	28 041 980-28
	Matte Black	28 041 980-33
	Brushed Champagne (22kt Gold)	28 041 980-46
	Champagne (22kt Gold)	28 041 980-47
	Brushed Chrome	28 041 980-93
	Brushed Dark Platinum	28 041 980-99

**Required miscellaneous**




- Concealed ceiling installation box 35 041 970 90 with ceiling fixing -**
- min. recess depth 90 mm
  - max. recess depth 115 mm
  - 2x female thread 1/2" outlet
  - concealed rough parts

## Rain shower for surface-mounted ceiling installation 300 x 240 mm - Platinum SERIES SPECIFIC

28 041 980 Product version from 5/1/2022

mm [inches]



### Flow rate chart



### Codes & Standards

DIN 4109

ISO 3822

Scottish Water  
Byelaws

UK Water Supply  
Regulations

Ü-Zeichen



## Rain shower for surface-mounted ceiling installation 300 x 240 mm - Platinum SERIES SPECIFIC

---


28 041 980 Product version from 5/1/2022

### Certificates and sustainability

---

LGA\_38

WRAS\_240502



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
1	90 17 20 263 00 90	fixing set	1.00	2
2	90 24 03 309 01 90	connection	1.00	2
3	90 24 03 309 00 90	connection	1.00	2