

## Shower head - Matte Black

28 505 979 Product version from 3/9/2015



- 155mm projection
- ball-joint pivotable through 18° (in any direction)
- Three or five settings: COMPACT RAIN, COMPACT SOFT FLOW, COMPACT AQUAPRESSURE FLOW, max. flow rate 7.6 l/min (at 3 bar)
- with anti-scale system
- spray head Ø 100mm
- rosette Ø 60 mm
- 1/2" connection
- Function from: 5.5 l/min
- WRAS

	Matte Black	28 505 979-33
	Chrome	28 505 979-00
	Brushed Platinum	28 505 979-06
	Platinum	28 505 979-08
	Dark Chrome	28 505 979-19
	Light Gold	28 505 979-26
	Brushed Light Gold	28 505 979-27
	Brushed Durabronze (23kt Gold)	28 505 979-28
	Brushed Bronze	28 505 979-42
	Brushed Champagne (22kt Gold)	28 505 979-46
	Champagne (22kt Gold)	28 505 979-47
	Brushed Chrome	28 505 979-93
	Brushed Dark Platinum	28 505 979-99

### Recommended miscellaneous




- Concealed wall elbow -**
- max. recess depth mm
  - min. recess depth mm

35 085 970 90


# Shower head - Matte Black

28 505 979    Product version from 3/9/2015

mm [inches]



Flow rate chart



## Codes & Standards

DIN 4109	ISO 3822	Scottish Water Byelaws	UK Water Supply Regulations
----------	----------	------------------------	-----------------------------

Ü-Zeichen



# Shower head - Matte Black

---

28 505 979    Product version from 3/9/2015


## Certificates

---

LGA\_28                      WRAS\_2201

# Shower head - Matte Black

28 505 979    Product version from 3/9/2015



## Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
1	09 27 22 045-33	rosette	1	30
2	90 14 10 026 00 90	seal	1	2
3	09 11 03 011-33	connection	1	30
4	90 14 20 002 00 90	seal	1	2
5	09 11 01 191-33	cover	1	30
6	90 12 05 055 00-33	shower	1	30