











## TARA ULTRA POT FILLER Cold-water valve - Brushed Durabron (23kt Gold)

TARA ULTRA

30 805 875



- 500mm projection
- pivoting spout
- laminar flow
- cold water only
- max. flow 5.7 l/min at 3 bar flow pressure
- min. recess depth 125 mm
- max. recess depth 80 mm
- lead-free
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB

	Brushed Durabron (23kt Gold)	30 805 875-28
	Chrome	30 805 875-00
	Brushed Platinum	30 805 875-06
	Platinum	30 805 875-08
	Durabron (23kt Gold)	30 805 875-09
	Dark Chrome	30 805 875-19
	Brushed Champagne (22kt Gold)	30 805 875-46
	Champagne (22kt Gold)	30 805 875-47
	Brushed Chrome	30 805 875-93
	Brushed Dark Platinum	30 805 875-99


### Required miscellaneous

**POT FILLER Concealed wall elbow** 35 087 970 90




- max. recess depth 125 mm
- min. recess depth 80 mm

30 805 875



Flow rate chart



Codes & Standards

DIN 4109

ISO 3822

NSF372

NSF61

Ü-Zeichen



## TARA ULTRA POT FILLER Cold-water valve - Brushed Durabross (23kt Gold)

TARA ULTRA


30 805 875

### Certificates

IAPMO\_N-4

IAPMO\_6

LGA\_29





TARA ULTRA POT FILLER Cold-water valve - Brushed Durabrass (23kt Gold)

TARA ULTRA

30 805 875

Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
	09 20 62 025-28	handle	13	20