

**xTOOL Concealed thermostat without volume control 1/2" - Champagne (22kt Gold)** SERIES SPECIFIC

36 501 985 Product version from 1/1/2022



- cover plate 120 x 120 mm
- temperature control handle with safety limit stop at 38°C
- thermostat cartridge
- WRAS

	Champagne (22kt Gold)	36 501 985-47
	Chrome	36 501 985-00
	Brushed Platinum	36 501 985-06
	Platinum	36 501 985-08
	Dark Chrome	36 501 985-19
	Brushed Light Gold	36 501 985-27
	Brushed Durabronze (23kt Gold)	36 501 985-28
	Matte Black	36 501 985-33
	Brushed Champagne (22kt Gold)	36 501 985-46
	Brushed Chrome	36 501 985-93
	Brushed Dark Platinum	36 501 985-99

**Required miscellaneous**

	<b>xTOOL Concealed thermostat module without volume control -</b> • min. recess depth 95 mm • max. recess depth 160 mm	35 503 970 90
--	--	---------------

**Recommended miscellaneous**


	<b>xGRID Attachment set for integrating in the dry wall construction -</b>	12 340 970 90
--	--	---------------

**Required miscellaneous**


	<b>xGRID Installation track 555 mm -</b>	12 360 970 90
--	--	---------------

**xTOOL Concealed thermostat without volume control 1/2" - Champagne (22kt Gold)** SERIES SPECIFIC

36 501 985 Product version from 1/1/2022  
mm [inches]



**Flow rate chart**



**Codes & Standards**

DIN 4109

EN 1111

ISO 3822

Scottish Water  
Byelaws

UK Water Supply  
Regulations

Ü-Zeichen



xTOOL Concealed thermostat without volume control 1/2" - Champagne (22kt Gold)

SERIES SPECIFIC

36 501 985    Product version from 1/1/2022

Certificates and sustainability

WRAS_2011	DVGW_DW-6512DN0	LGA_29
-----------	-----------------	--------

**xTOOL Concealed thermostat without volume control 1/2" - Champagne (22kt Gold)** SERIES SPECIFIC

36 501 985 Product version from 1/1/2022

