

## Rain shower with wall fixing FlowReduce 400 mm - Chrome

SERIES SPECIFIC

28 658 970 Product version from 4/1/2024



- rain shower Ø 400 mm
- PURE RAIN, max. flow rate 12 l/min (at 3 bar)
- Function from: 12 l/min
- with anti-scale system















### Technical data:

- 450mm projection
- rosette Ø 60 mm
- 1/2" connection

### Notes:

- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB

To be provided by the customer. Zigbee Gateway!

	Chrome	28 658 970-00
	Brushed Platinum	28 658 970-06
	Platinum	28 658 970-08
	Dark Chrome	28 658 970-19
	Light Gold	28 658 970-26
	Brushed Light Gold	28 658 970-27
	Brushed Durabronze (23kt Gold)	28 658 970-28
	Matte Black	28 658 970-33
	Brushed Dark Brass	28 658 970-39
	Brushed Bronze	28 658 970-42
	Brushed Champagne (22kt Gold)	28 658 970-46
	Champagne (22kt Gold)	28 658 970-47
	Brushed Chrome	28 658 970-93
	Brushed Dark Platinum	28 658 970-99


## Rain shower with wall fixing FlowReduce 400 mm - Chrome

SERIES SPECIFIC

28 658 970 Product version from 4/1/2024



Flow rate chart



### Codes & Standards

DIN 4109

ISO 3822

Ü-Zeichen



## Rain shower with wall fixing FlowReduce 400 mm - Chrome

SERIES SPECIFIC

28 658 970 Product version from 4/1/2024

Certificates and sustainability

LGA\_38

## Rain shower with wall fixing FlowReduce 400 mm - Chrome

SERIES SPECIFIC

28 658 970 Product version from 4/1/2024

Parts for other finishes can be found here: [Brushed Platinum](#)



## Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
7	90 12 05 090 20-00	shower	1.00	10
5	90 11 03 070 00-00	pipe	1.00	10
2	09 17 20 120 90	holder	1.00	2
4	09 27 97 015-00	rosette	1.00	10
1	04 30 31 032 00 90	fixing set	1.00	2
6	09 23 01 075 90	insert	1.00	2
8	90 30 09 069 00 90	key	1.00	2
3	09 14 10 150 90	seal	2.00	2