


- 210mm projection
- circular normal flow
- rotary diverter with volume control and shut-off function
- 3/8" shower outlet
- slide-on rosettes Ø 60 mm
- 1/2" connection
- gauge 150 mm - 15 mm
- max. flow 16.9 l/min at 3 bar flow pressure
- WRAS

Intrinsic protection against back flow.


	Light Gold	34 201 979-26
	Chrome	34 201 979-00
	Brushed Platinum	34 201 979-06
	Dark Chrome	34 201 979-19
	Brushed Light Gold	34 201 979-27
	Matte Black	34 201 979-33
	Brushed Dark Brass	34 201 979-39
	Brushed Bronze	34 201 979-42
	Brushed Champagne (22kt Gold)	34 201 979-46
	Champagne (22kt Gold)	34 201 979-47
	Brushed Chrome	34 201 979-93
	Brushed Dark Platinum	34 201 979-99

34 201 979 Product version from 9/1/2022

mm [inches]



### Flow rate chart



### Codes & Standards

DIN 4109

ISO 3822

Ü-Zeichen



## META Bath thermostat for wall mounting without shower set - Light Gold

---

META

34 201 979 Product version from 9/1/2022

Certificates and sustainability

---

LGA\_18

34 201 979 Product version from 9/1/2022

Parts for other  
finishes can be found  
here: [Chrome](#)

