

# WATER BAR Concealed body spray FlowReduce - Champagne (22kt Gold)

IMO

36 517 979



- HORIZONTAL RAIN, max. flow rate 6 l/min (at 3 bar)
- with anti-scale system
- cover plate 240 x 60 mm
- 1/2" connection
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB

Fits: IMO, LULU, MADISON, MEM, TARA, CL.1, LISSÉ, VAIA, META, CYO

|  |                               |               |
|--|-------------------------------|---------------|
|  | Champagne (22kt Gold)         | 36 517 979-47 |
|  | Chrome                        | 36 517 979-00 |
|  | Brushed Platinum              | 36 517 979-06 |
|  | Platinum                      | 36 517 979-08 |
|  | Dark Chrome                   | 36 517 979-19 |
|  | Light Gold                    | 36 517 979-26 |
|  | Brushed Light Gold            | 36 517 979-27 |
|  | Brushed Durabrass (23kt Gold) | 36 517 979-28 |
|  | Matte Black                   | 36 517 979-33 |
|  | Brushed Bronze                | 36 517 979-42 |
|  | Brushed Champagne (22kt Gold) | 36 517 979-46 |
|  | Brushed Chrome                | 36 517 979-93 |
|  | Brushed Dark Platinum         | 36 517 979-99 |

## Required miscellaneous



- Concealed wall installation box -** 35 206 970 90
- max. recess depth 173 mm
  - min. recess depth 100 mm

## Recommended miscellaneous



- xGRID Attachment set for integrating in the dry wall construction -** 12 340 970 90

## Required miscellaneous



- xGRID Installation track 555 mm -** 12 360 970 90

36 517 979


mm [inches]



**Flow rate chart**



**Trajectory diagram**



36 517 979

