









SYNC Profi single-lever mixer - Matte Black

33 865 895



- 200mm projection
- Flexible silicone hose with large operating range of up to 350 mm
- pivotable spout 360°
- Optional swivel limiter available with swivel limiter set 12 821 970 90
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB
- air-enriched flow and spray flow
- height of mixer 451 mm
- height up to aerator 119 mm
- hole diameter 35 mm
- sprayface with anti-scaling system
- max. flow 9.5 l/min at 3 bar flow pressure
- lead-free

Intrinsic protection against back flow.

	Matte Black	33 865 895-33
	Chrome	33 865 895-00
	Brushed Platinum	33 865 895-06
	Platinum	33 865 895-08
	Durabrass (23kt Gold)	33 865 895-09
	Dark Chrome	33 865 895-19
	Brushed Durabrass (23kt Gold)	33 865 895-28
	Brushed Champagne (22kt Gold)	33 865 895-46
	Champagne (22kt Gold)	33 865 895-47
	Brushed Chrome	33 865 895-93
	Brushed Dark Platinum	33 865 895-99

Recommended miscellaneous

Swivel limitation set - 12 821 970 90



Recommended miscellaneous

Strainer waste with control handle - Matte Black 10 712 970-33




Recommended miscellaneous

Dispenser without rosette - Matte Black 82 424 970-33




SYNC Profi single-lever mixer - Matte Black

33 865 895



Flow rate chart



Codes & Standards

DIN 4109

ISO 3822

Ü-Zeichen



SYNC Profi single-lever mixer - Matte Black

33 865 895

Certificates

LGA_29

SYNC Profi single-lever mixer - Matte Black

33 865 895

