

Shower thermostat for wall mounting - Brushed Bronze














SERIES SPECIFIC

34 442 979 Product version from 10/1/2023




- 3/8" shower outlet
- slide-on rosettes Ø 70 mm
- 1/2" connection
- gauge 150 mm - 13 mm
- with volume control
- WRAS

Intrinsic protection against back flow.


	Brushed Bronze	34 442 979-42
	Chrome	34 442 979-00
	Brushed Platinum	34 442 979-06
	Platinum	34 442 979-08
	Dark Chrome	34 442 979-19
	Light Gold	34 442 979-26
	Brushed Light Gold	34 442 979-27
	Brushed Durabrass (23kt Gold)	34 442 979-28
	Matte Black	34 442 979-33
	Brushed Dark Brass	34 442 979-39
	Brushed Champagne (22kt Gold)	34 442 979-46
	Champagne (22kt Gold)	34 442 979-47
	Brushed Chrome	34 442 979-93
	Brushed Dark Platinum	34 442 979-99

34 442 979 Product version from 10/1/2023

mm [inches]



Flow rate chart



Codes & Standards

DIN 4109

ISO 3822

Ü-Zeichen



Shower thermostat for wall mounting - Brushed Bronze

SERIES SPECIFIC

34 442 979 Product version from 10/1/2023

Certificates and sustainability

LGA_29

Shower thermostat for wall mounting - Brushed Bronze

SERIES SPECIFIC

34 442 979 Product version from 10/1/2023

Parts for other
finishes can be found
here: [Chrome](#)



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
	13 09 31 20 511-42	nipple	1.00	60
	3 90 30 40 010 00 90	regulator	1.00	2
	5 04 11 04 030 00 90	connection	2.00	2
	14 90 21 02 069 00-42	cover	1.00	30
	8 04 31 20 540 00 90	insert	1.00	2
	4 04 31 20 530 00 90	insert	1.00	2
	11 90 30 40 017 00 90	base	1.00	2
	12 90 14 10 010 00 90	seal	1.00	2
	6 90 31 20 512 00-42	rosette	2.00	30
	2 90 15 02 070 00 90	cartridge	1.00	2
	10 90 90 03 236 00 90	top	1.00	2
	7 09 29 30 050 90	sieve	2.00	2
	9 09 24 77 008-00	nut	2.00	10
	1 90 17 33 015 00-42	handle	2.00	30