

Concealed wall mounting -

35 003 970 90



- red brass, lead-free
- 2x female thread 1/2" connections
- dust cover
- anti-water packing
- soundproofing
- WRAS 2101023, 2003025

Can only be combined with exposed trim parts 26
024 661-FF / 36 013 660-FF / 36 045 660-FF / 36
013 970-FF / 36 045 970-FF / 36 804 661-FF.

Recommended miscellaneous



Extension 25 mm -
● Can only be combined with
exposed trim parts 36 804 661-FF.

12 179 970 90

Required miscellaneous




Drybox Concealed thermostat -
● Overflow is part of the scope of
delivery.

XS-08 3952


Concealed wall mounting -

35 003 970 90

mm [inches]



Flow rate chart



Codes & Standards

DIN 4109

EN 817

ISO 3822

Scottish Water
Byelaws

UK Water Supply
Regulations

Ü-Zeichen



Concealed wall mounting -

35 003 970 90

Certificates

WRAS_2101

DVGW_DW-
6512DN0

WRAS_2003


LGA_18

Concealed wall mounting -

35 003 970 90

Product version up to 10/2/2019

Product version from 10/2/2019





Concealed wall mounting -

35 003 970 90

Spare parts list

Product version up to 10/2/2019

Product version from 10/2/2019

No.	Item Number	Name	Quantity used	Delivery time
	05 30 31 029 00 90	fixing set	9	2