

Concealed thermostat with one function volume control - Brushed Champagne (22kt Gold)

SERIES SPECIFIC

36 425 670

Product version from 6/30/2022



- cover plate 150 x 90 mm
- temperature control handle with safety limit stop at 38°C
- hot water temperature limiter, can be preset
- WRAS

	Brushed Champagne (22kt Gold)	36 425 670-46
	Chrome	36 425 670-00
	Brushed Platinum	36 425 670-06
	Platinum	36 425 670-08
	Dark Chrome	36 425 670-19
	Brushed Light Gold	36 425 670-27
	Brushed Durabrass (23kt Gold)	36 425 670-28
	Matte Black	36 425 670-33
	Champagne (22kt Gold)	36 425 670-47
	Brushed Chrome	36 425 670-93
	Brushed Dark Platinum	36 425 670-99

Required miscellaneous



- Concealed thermostat -

35 425 970 90

 - max. recess depth 136 mm
 - min. recess depth 80 mm

Required miscellaneous



- Concealed thermostat with built-in isolators -

35 426 970 90

 - max. recess depth 136 mm
 - min. recess depth 80 mm




Concealed thermostat with one function volume control - Brushed Champagne (22kt Gold)


SERIES SPECIFIC

36 425 670 Product version from 6/30/2022

mm [inches]



Flow rate chart



Codes & Standards

DIN 4109	EN 1111	ISO 3822	Scottish Water Byelaws
UK Water Supply Regulations	Ü-Zeichen	VA-Zeichen	



Concealed thermostat with one function volume control - Brushed Champagne SERIES SPECIFIC
(22kt Gold)

36 425 670 Product version from 6/30/2022

Certificates and sustainability

LGA_19	ETA_20	DVGW_DW-6512DN0	LGA_19	WRAS_250402
--------	--------	-----------------	--------	-------------

Concealed thermostat with one function volume control - Brushed Champagne (22kt Gold) SERIES SPECIFIC

36 425 670 Product version from 6/30/2022

