

**Concealed thermostat with two function volume control - Light Gold**

**SERIES SPECIFIC**

36 426 970    Product version from 6/30/2022



- rotary diverter with volume control and shut-off function
- cover plate Ø 150 mm
- temperature control handle with safety limit stop at 38°C
- hot water temperature limiter, can be preset
- WRAS

	Light Gold	36 426 970-26
	Chrome	36 426 970-00
	Brushed Platinum	36 426 970-06
	Platinum	36 426 970-08
	Dark Chrome	36 426 970-19
	Brushed Light Gold	36 426 970-27
	Brushed Durabrass (23kt Gold)	36 426 970-28
	Matte Black	36 426 970-33
	Brushed Dark Brass	36 426 970-39
	Brushed Bronze	36 426 970-42
	Brushed Champagne (22kt Gold)	36 426 970-46
	Champagne (22kt Gold)	36 426 970-47
	Brushed Chrome	36 426 970-93
	Brushed Dark Platinum	36 426 970-99

**Required miscellaneous**



- Concealed thermostat -**
- min. recess depth 80 mm
  - max. recess depth 136 mm


35 425 970 90

**Required miscellaneous**




- Concealed thermostat with built-in isolators -**
- min. recess depth 80 mm
  - max. recess depth 136 mm

35 426 970 90



Flow rate chart



Codes & Standards

DIN 4109	EN 1111	ISO 3822	Scottish Water Byelaws
UK Water Supply Regulations	Ü-Zeichen	VA-Zeichen	



Concealed thermostat with two function volume control - Light Gold

SERIES SPECIFIC

36 426 970    Product version from 6/30/2022

Certificates and sustainability

---

LGA_19	ETA_20	DVGW_DW-6512DN0	LGA_19	WRAS_250402
--------	--------	-----------------	--------	-------------

